## [Jan-2018-Updated!Free 300-208 Exam PDF Offered by Braindump2go[Q107-Q117

2018 January new Cisco 300-208 Exam Dumps with PDF and VCE Free Updated Today! Following are some new added 300-208 Exam Questions: 1.|2018 New 300-208 Exam Dumps (PDF 7 VCE) 320Q&As Download:

https://www.braindump2go.com/300-208.html2.|2018 New 300-208 Exam Questions & Answers Download:

https://drive.google.com/drive/folders/0B75b5xYLjSSNdm14RFVqa0Q1YUU?usp=sharingQUESTION 107Which two Cisco ISE administration options are available in the Default Posture Status setting? (Choose two.)A. UnknownB. CompliantC. FailOpen D. FailCloseE. NoncompliantAnswer: BEQUESTION 108Which two portals can be configured to use portal FQDN? (Choose two.)A. adminB. sponsorC. guestD. my devicesE. monitoring and troubleshootingAnswer: BDQUESTION 109Which five portals are provided by PSN? (Choose five.) A. guest B. sponsor C. my devices D. blacklist E. client provisioning F. admin G. monitoring and troubleshootingAnswer: ABCDEOUESTION 110When you add a new PSN for guest access services, which two options must be enabled under deployment settings? (Choose two.)A. AdminB. MonitoringC. Policy ServiceD. Session ServicesE. ProfilingAnswer: CDQUESTION 111In Cisco ISE, which probe must be enabled to collect profiling data using Device Sensor?A. RADIUSB. SNMPQueryC. SNMPTrapD. Network ScanE. SyslogAnswer: AQUESTION 112Which two profile attributes can be collected by a Cisco Catalyst Switch that supports Device Sensor? (Choose two.)A. LLDP agent informationB. user agentC. DHCP optionsD. open portsE. operating systemF. trunk portsAnswer: ACQUESTION 113Which two profile attributes can be collected by a Cisco Wireless LAN Controller that supports Device Sensor? (Choose two.)A. LLDP agent informationB. user agentC. DHCP optionsD. open portsE. CDP agent informationF. FQDNAnswer: BCQUESTION 114 Which statement about Cisco ISE BYOD is true?A. Dual SSID allows EAP-TLS only when connecting to the secured SSID.B. Single SSID does not require endpoints to be registered.C. Dual SSID allows BYOD for guest users.D. Single SSID utilizes open SSID to accommodate different types of users.E. Single SSID allows PEAP-MSCHAPv2 for native supplicant provisioning. Answer: EQUESTION 115Which two types of client provisioning resources are used for BYOD implementations? (Choose two.)A. user agentB. Cisco NAC agentC. native supplicant profilesD. device sensorE. software provisioning wizardsAnswer: CEQUESTION 116Which protocol sends authentication and accounting in different requests?A. RADIUSB. TACACS+C. EAP-ChainingD. PEAPE. EAP-TLSAnswer: BOUESTION 117You enabled the guest session limit feature on the Cisco ISE. However, end users report that the same guest can log in from multiple devices simultaneously. Which configuration is missing on the network access device? A. RADIUS authentication B. RADIUS accounting C. DHCP required D. AAA overrideAnswer: B!!!RECOMMEND!!!1.|2018 New 300-208 Exam Dumps (PDF 7 VCE) 320Q&As Download: https://www.braindump2go.com/300-208.html2.|2018 New 300-208 Study Guide Video: YouTube Video:

YouTube.com/watch?v=yYAD1q-JEEY